

PROPERTIES

READY-MIX FINISH COAT FOR SEAMLESS CEILINGS AXACOUSTIC SOLUTIONS.

- Ready to use, odorless
- Very white
- Water-based product,
- Natural, made from cotton

HOW TO PREPARE

- Application on AXABOARD panels, covered with AXABASE.
- AXAFINISH Cotton should be mixed for 2-3 minutes in order to homogenize the coating before spray and used within 24h. AXAFINISH Cotton can be stored in the spray machine overnight by adding a little water and covering with plastic.
- Possible Dilution 0,5l / bucket of 15kg

HOW TO USE

- Plaster spraying machine with compressor (nozzle 4 or 5mm).
- The temperature of the room must be at least 10°C. Cover all surfaces near the spray area with plastic. Use moisture resistant tape.
- Smoothen/level in both directions directly after spraying. If necessary add a little water on the trowel.
- After complete drying, sanding is possible with abrasive grade 220.
- Clean the equipment with water.

TECHNICAL DATA

- **Aspect** : White paste, odorless
- **Usage** : 2 Kg/m² on AXABOARD covered with AXABASE
- **Drying Time** : 48 - 72 hours depending on thickness , at 20°C and normal humidity
- **Shelf Life** : 6 months in original, unopened packaging and stored away from frost and high heat.
- **Packaging** : Bucket of 15 Kg / Pallet of 33 buckets (495Kg)